



HRC-P6500

24

24

P6500

IP67

1.

24

2.

135

3.

4.

5.

6.

7.

8.

9.

IP67

10.

11.

	30 210 1/2.8" CMOS ICR
	0.02Lux @ (F1.6 AGC ON) 0.002Lux @ (F1.6 AGC ON)
	1/1 ~ 1/30,000
	52dB
	30x
(mm)	4.3mm 129mm
	F1.6 F4.4
(DxHxV)	Wide:67.8°x 59.8°x 40.5°;Tele:2.77°x 2.34°x 1.48°
	1M(wide) 1.5M(tele)
	3s
	H.264 Main Profile / Motion JPEG
	Full HD/1080P(1920x1080) + Full D1(720x480)
	25/30fps
	AF ZF (Zoom Trigger AF) MF
	/
	/ /
ICR	
	TCP/IP HTTP DHCP DNS DDNS RTP RTSP PPPoE SMTP NTP UPnP SNMP FTP 802.1x QoS HTTPS IPv6

	ONVIF, GB/T 28181
Web Service	WEB
API	SDK                      APP                      NVR      CMS
	SDHC
	384×288
	50mm
F	1.0
	60mk
	50Hz
	8~14um
	3s
	×2, ×4
	768×576
	/
	+
	DC: +8V~+15V
	H.264 Main Profile / Motion JPEG
	1    RJ45 10M/100M                      PoE                      802.3af
	1                      RS-485
	1
	1
	360°
	180°

	0.4 80°/S	0.4 80°/S
	128	
	/	/
	IP67 TV1500W	
	-40	65
	0 95%	
(Kg)	8.3	
	AC 24V	



C 13

0755-86518800 86518855

0755-2263 1700

QQ 76024879

<http://www.huaruicom.com>

